

New Arrivals Digital Overhead Stirrer

OS-26 Digital PRO Set

- Torque measuring Function
- Automatic reverse operation
- Touch Screen Colour LCD Display



OS-25 Digital Set

- Up to 70.000 mPas and 2.000 rpm
- With a Telescopic stand included
- High Fidelity LCD - Display backlit



Smart stirring at every turn. **Order Now**



Overhead Stirrer OS-25 Digital Set

Digital Fuzzy Controller

Delivers a smooth start and high precision when changing speed.

Anti-Trembling function

Provides and improves on impeller stability and safety

Large digital display

An easy and intuitive to read LCD display with backlight

Touch button and jog dial

Excellent design offers convenience and ease of use providing full control

Up to 70,000mPas, 2,000rpm

Powerful upgraded DC motor with Over-Heat, Over-Load and Over-Current protection

Telescopic stand

Ease of use and accurate setting with the space saving telescopic stand

Included in the Set

- Overhead Stirrer OS-25 Digital
- Impeller, 3 bladed, Ø50 mm
- Telescopic stand & clamp
- Chuck key & Spanner



Order Now

Overhead Stirrer OS-26 Digital PRO Set

Torque Measuring

Can measure Torque during operation in real time.

Rotation reverse function

Manually and automatic directly on the screen and programmable

Large colour touch screen

The wide display allows for easy set up and real time monitoring

9 Programs and 11 steps

Enables you to control the time, speed and forward/reverse rotation, providing total control

Up to 70,000mPas, 2,000rpm

Powerful upgraded DC motor with Over-Heat, Over-Load and Over-Current protection

Telescopic stand

Ease of use and accurate setting with the space saving telescopic stand

Included in the Set

- Overhead Stirrer OS-26 Digital PRO
- Impeller, 3 bladed, Ø50 mm
- Telescopic stand & clamp
- Chuck key & Spanner



Order Now

Model	OS-25 Set Art. Nr.: 6 290 025	OS-26 Pro Set Art. Nr.: 6 290 026
Stirring Capacity	Max. 25 Lit. (H2O)	
Maximum Viscosity	70,000 mPas	
Maximum Torque	120 Ncm	130 Ncm
Speed Range	100 to 2,000 rpm	30 to 2,000 rpm
Motor Rating (Input / Output)	110 / 85 W	200 / 160 W
Timer	99 hr 59 min	
Display	Digital LCD Display with backlight	3,5" touch Colour LCD Display
Controller	Digital Fuzzy Controller with Touch button & Jog Dial	Digital PID Feedback Control High Performance MCU
Max. Impeller Shaft Diameter	10 mm	
Program Operation	/	9 Programm, 11 Steps
Working Direction	/	Forward and reverse
Others – Special function	/	Torque measuring function in real time real time monitoring by USB port
Permissible Temp. & Humidity	0 ~ 40°C, 80%	
Safety Device	Overload & Heat Protector for Motor	Overload & Heat Protector for Motor Error code Display
Material	ABS and Aluminium	
Power Consumption	180 W	280 W
Dimension (w x d x h) & Net Weight	80 x 194 x 245, 10,39 Kg	80 x 185 x 260, 10,50 Kg
Power Supply & Cord Plug	1 Phase, AC 120V, 60Hz or AC 230V, 50/60Hz, with Cord/Plug	

